

es-te Berlin estefold finish strong



estefold 4210's characteristics are:

- Single pass offline folder
- Highest throughput
- Outrageously dependable







Features

estefold 4210 shows its full strength when plans from different printers have to be folded

Time consuming fold work is done with outstanding precision and speed.

The finished fold packages are automatically deployed face up on the conveyor belt where they can be obtained in an ergonomic height. Only a few minutes practice are sufficient to utilize its full potential.

Technical Data

Passes for full fold Folding speed 19 m/min Document lenght (Fan Fold only) 400 mm - 6000 mm Document lenght (Fan- and Cross fold) 400 - 2500 mm (80g/m² DIN) Media width 297 - 930 mm Media weight 60 - 120 g/m²

Panel width 180 - 210 mm 297 mm* Panel height Margin o - 30 mm Fold programs

Options

Fold Away Feed Table

The Fold Away Feed Table offers the advantage that it can be easily flipped down when the estefold 2300 is not in use. The footprint is therefore reduces by approx. 50%.

Tab applicator

The tab applicator allows to automatically apply tear resistant, pre-punched tabs to the folded drawing. It ensures that prints are easily filed for good. The tabs come in easy to change rolls.

Cross Fold 297/ 305 mm

Cross Fold 297/305 mm allows to select between a cross fold length of 297 mm or 305 mm. It is most useful to fold 36" wide documents into three equally high panels, or 610 mm wide documents into two equal panels.

Optional 305 mm

⁴ pre-programed-, 4 editable fold programs (calculated and uncalculated)